

Prodigi™ Classic 10-10 (E/G)

Electric or Gas

UL

Engineered for dependability and cost savings, Prodigi™ Classic combination ovens are an all-in-one solution for efficient and consistent food production. These ovens do the work of a convection oven, kettle, steamer, fryer, and more. With labor-saving features, Prodigi Classic combination ovens are designed to support the most demanding kitchens.

Standard features

- Boilerless steam generation
- Absolute Humidity Control™ for selecting any humidity level from 0-100% to maximize food quality, texture, and yield
- Three cooking modes—steam, convection, and combination
- 7" programmable, touchscreen control
- Easy recipe upload/download via USB port
- Four fully automated cleaning cycles
- Front-accessible and retractable rinse hose
- Zero clearance design



10-10 Classic



CAPACITY

11

Eleven* full size hotel or GN 1/1 pans;
Ten half-size sheet pans, one row deep
[*one less on models with smokers]

Two side racks with eleven non-tilt support rails;
11-3/4" [298mm] horizontal width between rails,
2-3/4" [70mm] vertical spacing between rails

120 lb (54 kg) product maximum

75 quarts (95 liters) volume maximum

Five (5) wire shelves included.

Copper Installation kits

Base kit selection on amp draw found in electrical table

Electric

- 20A [5026970]
- 30A [5026932]
- 40A [5026972]
- 50A [5026973]
- 80A [5026974]

Gas

- 20A [5026980]
- 30A [5026933]
- No cord [5026971]

CPVC Installation kits

Base kit selection on amp draw found in electrical table

Electric

- 20A [5021521]
- 30A [5021519]
- 40A [5021525]
- 50A [5021526]
- 80A [5021527]
- 125A [5021529]
- 150A [5021530]
- 200A [5021531]
- 250A [5021531]

Gas

- 20A [5021522]
- 30A [5021520]
- No cord [5021524]

Condensable Particulate Matter (CPM) emissions produced through the most aggressive testing methods available were measured at 0.77 mg/m³ for 11,660 beef patties which is below the maximum allowable level of 5.0 mg/m³ established by EPA test method 202. This product is UL listed under KNLZ in the U.S. and Canada.



COA# 5760
Electric models only

ANSI/NSF 4

ANS 203.11-2014 1-8-2002

Accessories [reference accessory catalog]



Security devices for correctional facility use

- Optional base package (not available with recessed door): includes tamper-proof screw package
- Anti-entrapment device [5017157] (optional)
- Control panel security cover [5017144] (optional)
- Hasp door lock (padlock not included) [5017145] (optional)

Water treatment

- RO System OPS175CR/5 [5031203]

Extended warranty

- One-year warranty extension


Installation options (select one)

- Alto-Shaam Factory Authorized Installation Program — available in the U.S. and Canada only
- Installation Start-Up Check — available through an Alto-Shaam authorized service agency

ProdiGi™ Classic 10-10 (E/G)

ALTO-SHAAM®

DIMENSIONS — standard door



Model	Exterior (H x W x D)	Interior (H x W x D)	Net Weight
10-10	46" x 35-11/16" x 40-1/16" [1169mm x 906mm x 1018mm]	31-1/2" x 16-1/4" x 28-1/16" [800mm x 413mm x 713mm]	625 lb (283 kg)

Ship Dimensions (L x W x H)*



56" x 45" x 65" [1422mm x 1143mm x 1651mm]

*Domestic ground shipping information. Contact factory for export weight and dimensions.

OVENS WITH VENTECH® HOOD

Electric only

Eliminate the need for a traditional kitchen hood. Ventech Type 1 hoods with condensation technology condense steam while capturing and removing grease-laden air, vapors, and lingering smoke. For more demanding locations, Ventech PLUS™ hoods include a HEPA filter. These hoods combine the fine particulate filtering of a HEPA filter with condensation technology of the standard Ventech hood.




Model	Ventech Hood Exterior (H x W x D)	Net Weight	Ship Dimensions (L x W x H)*	Ship Weight*
VH-20	11-1/8" x 35-7/8" x 41-5/8" [282mm x 911mm x 1058mm]	158 lb (72 kg)	56" x 49" x 20" [1422mm x 1245mm x 508mm]	276 lb (125 kg)
Ventech Hood Plus Exterior (H x W x D)	17-1/8" x 35-7/8" x 41-5/8" [435mm x 911mm x 1058mm]	211 lb (96 kg)	Ship Dimensions (L x W x H)*	Ship Weight*
Oven with Ventech Hood (H x W x D)	54-1/8" x 35-7/8" x 41-11/16" [1376mm x 911mm x 1059mm]	Net Weight	59" x 49" x 20" [1500mm x 1245mm x 508mm]	336 lb (152 kg)
Oven with Ventech Hood Plus (H x W x D)	60-1/8" x 35-7/8" x 41-11/16" [1527mm x 911mm x 1059mm]	Net Weight	Ship Dimensions (L x W x H)*	Ship Weight*
		Call factory	56" x 45" x 65" [1422mm x 1143mm x 1651mm]	Call factory
			Ship Dimensions (L x W x H)*	Ship Weight*
			56" x 45" x 65" [1422mm x 1143mm x 1651mm]	Call factory

*Domestic ground shipping information. Contact factory for export weight and dimensions.

Prodigi™ Classic 10-10 (E/G)

ALTO-SHAAM®

DIMENSIONS — recessed door



Model
10-10

Exterior (H x W x D)
46" x 39-15/16" x 40-1/16" (1169mm x 1015mm x 1018mm)

Ship Dimensions (L x W x H)*

56" x 45" x 65" (1422mm x 1143mm x 1651mm)

*Domestic ground shipping information. Contact factory for export weight and dimensions.

Interior (H x W x D)
31-1/2" x 16-1/4" x 28-1/16" (800mm x 413mm x 713mm)

Net Weight
625 lb (283 kg)

Ship Weight

695 lb (315 kg)

Prodigi™ Classic 10-10 (E/G)

ALTO-SHAAM.



10-10E ELECTRIC

10-10E	V	Ph	Hz	Awg (IEC)	Standard Power			Connection
					A	Breaker	kW	
208–240V	208	3	50/60	4	39.4	40	14.2	3Ø/PE
	240	3	50/60	4	45.5	50	18.9	3Ø/PE
440–480V	440	3	50/60	8	20.8	25	16.2	3Ø/PE
	480	3	50/60	8	22.7	25	18.9	3Ø/PE

- Electrical connections must meet all applicable federal, state, and local codes.
- For use on individual branch circuit only.
- Ovens are not supplied with an electrical cord or plug.
- For CE models use a Type B current protection device that accommodates a leakage current of 30mA.

Heat of rejection

10-10E	BTU/hr	kW
	1,131	0.33



10-10G ELECTRIC

†	10-10G	V	Ph	Hz	Awg (IEC)	A	Breaker	kW	Connection
†	120V	120	1	60	12	7.0	20	0.84	1Ø/PE
		208–240V	3	50/60	14	4.8	15	1.0	3Ø/PE
			3	50/60	14	4.2	15	1.0	3Ø/PE

† Per UL requirements, must be permanently connected to electrical supply source

Heat of rejection

10-10G	BTU/hr	kW
	448	0.13



Prodigi™ Classic 10-10 (E/G)

ALTO-SHAAM®



Top: 20" [508mm]
 Left: 0" [0mm]
 18" [457mm] recommended service access
 Right: 0" [0mm] non-combustible surfaces
 2" [51mm] combustible surfaces
 Bottom: 5-1/8" [130mm]
 Back: 4" [102mm] between plumbing and nearest object



- Oven must be installed level.
- Oven must be installed on noncombustible surface.
- Use a water supply shut-off valve and back-flow preventer when required by local code.
- Exhaust hood installation is required on gas-heated models.
- Drain must not be located directly underneath the appliance unless a stand with solid top or shelf is used.



Heat of rejection

10-10E	Heat Gain qs, BTU/hr	Heat Gain qs, kW
	968	0.28



Noise emissions

Without hood system, a maximum 67 dBA was measured at 3.3 ft [1 m] from unit.

With hood system, a maximum 81 dBA was measured at 3.3 ft [1 m] from unit.



Heat of rejection

10-10G	Heat Gain qs, BTU/hr	Heat Gain qs, kW
	392	0.11



Noise emissions

Without hood system, a maximum 67 dBA was measured at 3.3 ft [1 m] from unit.

With hood system, a maximum 81 dBA was measured at 3.3 ft [1 m] from unit.



Gas Requirements

- Gas type must be specified on order
- Hook-up: 3/4" NPT

UL Marked Appliances	Maximum Input BTU/h	Minimum Input BTU/h	Maximum Inlet Pressure Inches WC [kPa]	Minimum Inlet Pressure Inches WC [kPa]	Maximum Fuel Consumption*	
					CFH	GPH
Natural Gas	70,000	57,000	14.0 [3.5]	5.5 [1.1]	76.2	N/A
Propane	70,000	48,000	14.0 [3.5]	9.0 [2.8]	32.0	0.9

*Assumes an average heating value for natural gas to be 1050 BTU/SCF and a specific gravity of 0.60. The assumed value for propane gas is 2,500 BTU/SCF, and a specific gravity of 1.53.



Water requirements (per oven)

Two cold water inlets — drinking quality

- One treated water inlet: 3/4" NPT male connection. Line pressure 30 psi minimum dynamic and 90 psi maximum static [200–1000 kPa] at a minimum flow rate of 0.26 gpm [1 L/min].
- One untreated water inlet: 3/4" NPT male connection. Line pressure 30 psi minimum dynamic and 90 psi maximum static [200–1000 kPa] at a minimum flow rate of 2.64 gpm [10 L/min]. Water drain: 1-1/2" [40mm] connection with a vertical vent to extend above the exhaust vent. Materials must withstand temperatures up to 200°F [93°C].



Clearance requirements for water filtration system

Do not install a water filtration system behind unit.

Water Quality Standards

It is the sole responsibility of the owner/operator/purchaser of this equipment to verify that the incoming water supply is comprehensively tested and, if required, a means of "water treatment" provided that would meet compliance requirements with the published water quality standards shown below. Non-compliance with these minimum standards will potentially damage this equipment and/or components and void the original equipment manufacturer's warranty. Alto-Shaam recommends using the Alto-Shaam Reverse Osmosis System to properly treat your water.

Inlet Water Requirements		
Contaminant	Treated Water	Untreated Water
Free Chlorine	Less than 0.1 ppm [mg/L]	Less than 0.1 ppm [mg/L]
Hardness	30-70 ppm	30-70 ppm
Chloride	Less than 30 ppm [mg/L]	Less than 30 ppm [mg/L]
pH	7.0 to 8.5	7.0 to 8.5
Silica	Less than 12 ppm [mg/L]	Less than 12 ppm [mg/L]
Total Dissolved Solids [tds]	50-125 ppm	50-360 ppm

CONTACT US

W164 N9221 Water Street | Menomonee Falls, Wisconsin 53051 | U.S.A.

Phone: 262.251.3800 | 800.558.8744 U.S.A./Canada | Fax: 262.251.7067 | alto-shaam.com