



Project: _____

Location: _____

Item #: _____ Quantity: _____

Model #: _____

MODEL: **IUC-UC48F****UNDERCOUNTER:**
*Undercounter Freezers***General Strengths**

- ✓ **Energy efficiency higher.** R290 refrigerant with electric fans and evaporative tray without electric resistances.
- ✓ **Sanitation.** The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- ✓ **Doors.** Self-closing door system with permanent pressure. Stay open feature included when door remains open after 95 degrees. All doors include triple chamber door gaskets, easy to remove and snap in.
- ✓ **Control systems.** Greater ability for the adjustment of temperature range as per the end user's requirements.
- ✓ **100% Tested.** All condenser units are 100% tested, in helium chambers for refrigerant leak detections.
- ✓ **Certified.** Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2015 (Quality); ISO 14001:2015 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)



UNIT TOTAL HEIGHT				
UNIT	LENGTH	DEPTH	2" CASTER HEIGHT	4" CASTER HEIGHT
IUC-UC48F	48-1/8	30-1/8	Optional	Standard
			32-11/16	35-3/4

MODEL	Dimensions (inches) (mm)			Nº Doors	Nº Shelves	Ref.	Ref. Weight (Lbs.) (gr.)	Temp. Range (°F) (°C)	Capacity (Cu. Ft.) (L)	Cond. Unit. H.P.	Case Amps 115 V.	Crated Weight (Lbs.) (Kg.)
	W	D	H									
IUC-UC48F	48-1/8 1227	30-1/8 765	35-3/4 910	2	4	R290	0.24 110	33°F/38°F 0°C/4°C	14 396	1/2	4.5	360 163

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE



Infrico USA Corp.
1409 N.W. 84th Avenue
Doral, FL 33126
1.305.777.9599 Office
1.305.777.9598 Fax

www.infrico.us
sales@infrico.com

APPROVALS: _____

AVAILABLE AT: _____



Project: _____

Location: _____

Item #: _____ Quantity: _____

Model #: _____

MODEL: **IUC-UC48F**

UNDERCOUNTER:
Undercounter Freezers

STANDARD FEATURES

➤ Exterior

- AISI 430 Stainless Steel,
- AISI 304 Stainless Steel Top.

➤ Interior

- AISI 430 Stainless Steel.

➤ Doors

- Polyurethane insulated doors,
- Self closing doors with stay open feature,
- Stainless Steel heavy-duty hinges,
- Triple chamber snap in door gaskets for easy removal and cleaning,
- **Heated door frames to avoid accumulation of ice,**
- Full-height door opening: 19-5/8" x 21-7/8" (500x555 mm).

➤ Insulation

- CFC-Free polyurethane insulation, entire cabinet structure is foamed-in using a high-density polyurethane insulation,
- Low GWP & Zero ODP effect.

OPTIONAL FEATURES

- ✓ Single Overshelf kit.
- ✓ Double Overshelf kit,
- ✓ 4" Backsplash,
- ✓ Set of 2" diameter casters, with lock provided on front set,
- ✓ Electrical connection is 230 V / 1ph / 50 Hz (plug type varies).

➤ Shelving

- (2) Plastic coated wire shelves per section,
- Set of Stainless Steel shelf brackets,
- Easy remove for cleaning,
- Dimensions WxD: 21" x 17" (533x432 mm).

➤ Casters

- 4" diameter casters,
- Locks provided on front set.

➤ Refrigeration

- Temperature regulated by thermostatic control,
- Temperature display,
- Hot gas defrost,
- Energy-saving non-electric condensate pan,
- Evaporator coil coated with anti-corrosion material 100% Polyester,
- Forced air refrigeration system,
- Expansion valve,
- Electric fans,
- Refrigeration capacity: 1456 Btu/h (-22°F) / 427 W (-30°C).

➤ Electrical


- Cord and NEMA 5-15P plug.
- Electrical connection is 115V / 1ph / 60 Hz.
- 20 AMP breakers required,




➤ ETL Listed to UL471 Standard and Sanitation classified to NSF7.

PLAN VIEW


ELEVATION



RIGHT VIEW



PLAN VIEW



ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

Revision: 02

Date: 09/09/2023

IUC-UC48F_FT_69_1



AUTODESK
REVIT



Infrico USA Corp.
1409 N.W. 84th Avenue
Doral, FL 33126
1.305.777.9599 Office
1.305.777.9598 Fax

www.infrico.us
sales@infrico.com

APPROVALS: _____

AVAILABLE AT: _____