

## STANDARD FEATURES

### ⌘ DURABLE STAINLESS STEEL

Our megatops boast a sturdy stainless steel exterior and interior finish and galvanized back panel providing strength and durability.

### ⌘ ERGONOMICALLY DESIGNED SOLID DOORS

Standard doors come with easy grip handles and self closing/120 ° stay open door feature, working together for customer convenience.

### ⌘ MAGNETIC DOOR GASKET

Built of one piece, the gasket is removable without tools for ease of cleaning and replacement. Door's in step design gives added protection to the gasket.

### ⌘ EFFICIENT REFRIGERATION SYSTEM

Factory engineered oversized and balanced refrigeration system. CFC-free R-134A Refrigerators maintain temperature from 33°F to 41°F. Forced air design underneath pans to keep products fresh.

### ⌘ FRONT BREATHING

Allows unrestricted placement of the unit.

### ⌘ HIGH DENSITY POLYURETHANE INSULATION

2" Ecomate® CFC-free polyurethane insulation foamed in place for extra strength and energy efficiency, while being environmentally friendly with zero ozone depletion potential (ODP) and zero global warming potential (GWP).

### ⌘ INSULATED LIDS

Removable insulated lids keep food fresh and cold by reducing condensation.

### ⌘ REVERSIBLE & EASY CLEANING CUTTING BOARD

The full length removable white polyethylene cutting board provides a comfortable 10" operation space.

### ⌘ STANDARD WITH FULL SETS OF 1/6th PANS, 4" DEEP

It also accomodate 6" deep pans (except for APTM-27: has three 1/9th size pans).

## OPTIONS & ACCESSORIES

Additional epoxy coated shelves / 2.5" Casters /  
6" Adjustable stainless steel legs / 220V-50 cycles- 1 phase

□ APTM-27-12

□ APTM-60-24

□ APTM-48-18

□ APTM-70-32



APTM-27-12



APTM-48-18



APTM-72-30




ISO 9001

MODEL	DOORS	TOP PANS	SHLVs.	AMPS	HP	VOLTAGE	NEMA PLUG	CORD LENGHT	CABINET L	DIMENSIONS D*	H**	SHIPPING Wt.	Cubes
REFRIGERATOR													
APT-27-12	1	12	1	5.1	1/6	115/60/1	5-15P	8'	27"	34"	41-5/8"	225	36
APT-48-18	2	18	2	6.0	1/4	115/60/1	5-15P	8'	48"	34"	41-5/8"	327	55
APT-60-24	2	24	2	7.3	1/3	115/60/1	5-15P	8'	60"	34"	41-5/8"	380	73
APT-72-30	3	30	3	8.0	1/3	115/60/1	5-15P	8'	72"	34"	41-5/8"	465	87


\* Depth does not include 1" rear bumper

\*\*Height does not include 5" overall for casters


APT-27-12 Top




APT-48-18 Top




APT-60-24 Top




APT-70-32 Top




APT-27-12 Front




APT-48-18 Front




APT-60-24 Front




APT-70-32 Front



APT-27-12 Common View




Open Lid



Closed Lid

## \* Specifications



### ④ CABINET CONSTRUCTION

- EXTERIOR: Stainless steel, galvanized steel back.
- INTERIOR: Stainless steel.
- CABINET & DOOR : Entire foamed-in-place high-density, Ecomate® CFC-free, polyurethane insulation. Coved corner floor to meet NSF requirements.
- CASTERS: 4" Diameter swivel casters, front two with brakes.
- SHELVES: 1 Adjustable heavy duty epoxy coated wire shelves per door.

### ④ DOORS

- Stainless steel exterior with ABS interior liner.
- One piece constructions magnetic gasket, removable without tools for easy cleaning.
- Self-closing doors with 120° stay open feature and recessed handles for convenient loading and unloading.

### ④ REFRIGERATION SYSTEM

- Oversized and balanced refrigeration system.
- R-134A holding temperature at 33°F to 41°F Refrigerators.
- Self-contained capillary tube system using environmentally-friendly and CFC-free refrigerant.
- Front breathing allows unrestricted placement of the unit.
- Large fan motor and fan blades for better air circulation.
- Self contained system, no plumbing necessary.

### ④ ELECTRICAL

- The whole unit is completely pre-wired at factory with cord and plug set included and ready for final connection to a 115/60/1 phase.
- 220V / 50Hz / 1Ph available from factory.

### ④ WARRANTY

Continental USA & Canada:

- **One year** labor and parts warranty.
- **Five year** compressor warranty.
- **International:** one year parts only.

\* Asber's specification are subject to change without notice as we continue to make product improvements.